



ADVENTURE POWER[®]

UPG No. 42005

HUB16A-A Conventional Battery

This battery is specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS, high vibration resistant and long cycle life.

Specification

Nominal Voltage	12 Volts
Nominal Capacity (10H-R)	16 Ah
Approximate Weight (With Acid)	11.02 lbs. (5 kgs)
Recommended Maximum Charging Current Limit	4.8A
Equalization and Cycle Service	14.8 VDC/unit Average at 25°C
Cycle Life (JIS D 5302:2004)	325
Terminal Type	G



Physical Dimensions: in (mm)

	<h4>Terminal Configuration</h4>	<h4>Polarity</h4> <h4>Exhaust</h4>
<p>L: 5.91" (150mm) H: 7.09" (180mm) W: 3.54" (90mm) All data subject to change without notice.</p>		



Front



Side



Terminals

Filling Instructions

- ⊕ Before filling, ensure your new battery is the correct size for your vehicle.
- ⊕ Once the battery is filled, it cannot be returned to vendor.
- ⊕ Only use the acid pack that comes with your battery.
- ⊕ Fill all cells to the "FULL" mark and wait 30 minutes.
- ⊕ After 30 minutes, any cell that has settled below the "FULL" mark should be topped off to the "FULL" mark.
- ⊕ Replace the sealer caps before charging the battery.

Charging Instructions

- ⊕ Charge the battery fully before installing.
- ⊕ Never charge this battery with a charger that delivers more than 5 amps of current. Larger chargers will harm the battery.
- ⊕ For optimum performance, UPG recommends charging and maintaining with the Energizer[®] Maintainer 4000 battery charger.
- ⊕ This charger/ maintainer can remain connected to the battery indefinitely.

www.upgi.com