



# UPG ADVENTURE POWER<sup>®</sup>

STAY POWERED<sup>®</sup>

The battery is constructed by plates, separators, safety valves and container. Since the electrolyte is held by a glass mat separator and plates, the battery can be used without leakage. It's specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS and high vibration resistance.

UPG No. 42009

## UT5L

### Sealed AGM Battery

#### Specification

|   |                               |
|---|-------------------------------|
| <b>Nominal Voltage</b>                            | 12 Volts                      |
| <b>Nominal Capacity (10H-R)</b>                   | 4 Ah                          |
| <b>Approximate Weight (With Acid)</b>             | 4.19 lbs. (1.9 kgs)           |
| <b>Recommended Maximum Charging Current Limit</b> | 1.2A                          |
| <b>Equalization and Cycle Service</b>             | 14.8 VDC/unit Average at 25°C |
| <b>Terminal Type</b>                              | D                             |



#### Physical Dimensions: in (mm)

**L:** 4.49" (204mm) **H:** 4.21" (107mm) **W:** 2.76" (70mm)  
All data subject to change without notice.

#### Terminal Configuration

#### Polarity



Front



Side



Terminals

#### Charging Instructions

- Ensure your battery is the correct size for your vehicle.
- This battery is sealed at the factory and is maintenance-free. Do NOT open or attempt to fill this battery.
- Charge the battery fully before installing.
- Never charge the battery with a charger that delivers more than 1 amp of current. Larger chargers will harm the battery.
- For optimum performance, UPG recommends charging and maintaining with the Energizer<sup>®</sup> Maintainer 1000 battery charger.
- This charger maintainer can remain connected to the battery indefinitely.

*Energizer<sup>®</sup> and the related graphics are trademarks of Eveready Battery Company, Inc. and are used under license by UPG.*

[www.upgi.com](http://www.upgi.com)

1720 Hayden Drive | Carrollton, Texas 75006 | P 469.892.1122 | T 866.892.1122 | F 469.892.1123 | [sales@upgi.com](mailto:sales@upgi.com)