



UPG ADVENTURE POWER®

STAY POWERED®

The battery is constructed by plates, separators, safety valves and container. Since the electrolyte is held by a glass mat separator and plates, the battery can be used without leakage. It's specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS and high vibration resistance.

UPG No. 42011

UTX7L


Sealed AGM Battery

Specification

Nominal Voltage	12 Volts
Nominal Capacity (10H-R)	6 Ah
Approximate Weight (With Acid)	5.51 lbs. (2.5 kgs)
Recommended Maximum Charging Current Limit	1.8A
Equalization and Cycle Service	14.8 VDC/unit Average at 25°C
Terminal Type	D



Physical Dimensions: in (mm)



L: 4.49" (204mm) **H:** 5.20" (132mm) **W:** 2.76" (70mm)
All data subject to change without notice.

Terminal Configuration



Polarity



Front



Side



Terminals

Charging Instructions

- Ensure your battery is the correct size for your vehicle.
- This battery is sealed at the factory and is maintenance-free. Do NOT open or attempt to fill this battery.
- Charge the battery fully before installing.
- Never charge the battery with a charger that delivers more than 2 amps of current. Larger chargers will harm the battery.
- For optimum performance, UPG recommends charging and maintaining with the Energizer® Maintainer 2000 battery charger.
- This charger maintainer can remain connected to the battery indefinitely.

Energizer® and the related graphics are trademarks of Eveready Battery Company, Inc. and are used under license by UPG.

www.upgi.com

1720 Hayden Drive | Carrollton, Texas 75006 | P 469.892.1122 | T 866.892.1122 | F 469.892.1123 | sales@upgi.com