



The battery is constructed by plates, separators, safety valves and container. Since the electrolyte is held by a glass mat separator and plates, the battery can be used without leakage. It's specially designed as a high-performance battery used for motorcycles. The characteristics are high cranking AMPS and high vibration resistance.

Specification

Nominal Voltage	12 Volts
Nominal Capacity (10H-R)	8 Ah
Approximate Weight (With Acid)	6.61 lbs. (3 kgs)
Recommended Maximum Charging Current Limit	2.4A
Equalization and Cycle Service	14.8 VDC/unit Average at 25°C
Terminal Type	D



Physical Dimensions: in (mm)

L: 5.94" (151mm) **H:** 4.13" (105mm) **W:** 3.43" (87mm)
All data subject to change without notice.

Terminal Configuration

Polarity



Front



Side



Terminals

Charging Instructions

- Ensure your battery is the correct size for your vehicle.
- This battery is sealed at the factory and is maintenance-free. Do NOT open or attempt to fill this battery.
- Charge the battery fully before installing.
- Never charge the battery with a charger that delivers more than 2 amps of current. Larger chargers will harm the battery.
- For optimum performance, UPG recommends charging and maintaining with the Energizer[®] Maintainer 2000 battery charger.
- This charger maintainer can remain connected to the battery indefinitely.

Energizer[®] and the related graphics are trademarks of Eveready Battery Company, Inc. and are used under license by UPG.